

超微粒鎢鋼麻花鑽頭

Jobber Drills

118° Point for Quick Penetration

MG
CarbideUncoated
Bright

Code No: D453-DC



Work Material

P	H	M	K	N	S
○			●	●	

P	鋼鐵 Steel
---	-------------

K	鑄鐵 Cast Iron
---	-----------------

N	鋁 Aluminium
---	----------------

N	銅 Copper
---	-------------

N	塑膠 Plastics
---	----------------

N	複合材料 FRP CFRP Composite Material
---	-------------------------------------


Tolerance: DC

All Sizes: h7

Feature of product:

提供卓越的耐磨性。

用於抗拉強度較低的材料，如：鑄鐵、鑄鋁、青銅、銅、鋅、黃銅、橡膠、塑膠及複合材料等。鋼鐵也可適用於一般鑽孔加工。



Standard Length

Dc h7	Lc mm	L mm	Bright D453
0.5	6	30	●
0.6	6	30	●
0.7	8	30	●
0.8	10	30	●
0.9	16	38	●
1	19	38	●
1.1	19	38	●
1.2	19	38	●
1.3	19	38	●
1.4	19	38	●
1.5	19	38	●
1.6	19	38	●
1.7	19	38	●
1.8	22	44	●
1.9	22	44	●
2	22	44	●
2.1	22	44	●
2.2	25	51	●
2.3	25	51	●
2.4	25	51	●
2.5	25	51	●
2.6	32	57	●
2.7	32	57	●
2.8	32	57	●
2.9	32	57	●
3	32	57	●
3.1	32	57	●
3.2	32	57	●
3.3	35	64	●
3.4	35	64	●
3.5	35	64	●
3.6	35	64	●
3.7	35	64	●
3.8	35	64	●
3.9	35	64	●
4	35	64	●
4.1	35	64	●
4.2	35	64	●
4.3	41	70	●
4.4	41	70	●
4.5	41	70	●
4.6	41	70	●

Jobber Drills
118° Point for Quick Penetration

MG
Carbide

Uncoated
Bright



Code No: D453-DC

Standard Length

Work Material

P	H	M	K	N	S
○	□	□	●	●	□

P 鋼鐵
Steel

K 鑄鐵
Cast Iron

N 鋁
Aluminium

N 銅
Copper

N 塑膠
Plastics

N 複合材料 FRP CFRP
Composite Material

Tolerance: DC

All Sizes: h7

Feature of product:

提供卓越的耐磨性。

用於抗拉強度較低的材料，如：鑄鐵、鑄鋁、青銅、銅、鋅、黃銅、橡膠、塑膠及複合材料等。鋼鐵也可適用於一般鑽孔加工。

Dc H7	Lc mm	L mm	Bright D453
4.7	41	70	●
4.8	41	70	●
4.9	41	70	●
5	44	76	●
5.1	44	76	●
5.2	44	76	●
5.3	44	76	●
5.4	44	76	●
5.5	44	76	●
5.6	44	76	●
5.7	44	76	●
5.8	44	76	●
5.9	51	83	●
6	51	83	●
6.1	51	83	●
6.2	51	83	●
6.3	51	83	●
6.4	51	83	●
6.5	51	83	●
6.6	54	89	●
6.7	54	89	●
6.8	54	89	●
6.9	54	89	●
7	54	89	●
7.1	54	89	●
7.2	54	89	●
7.3	54	89	●
7.4	54	89	●
7.5	60	95	●
7.6	60	95	●
7.7	60	95	●
7.8	60	95	●
7.9	60	95	●
8	60	95	●
8.1	60	95	●
8.2	60	95	●
8.3	64	102	●
8.4	64	102	●
8.5	64	102	●
8.6	64	102	●
8.7	64	102	●
8.8	64	102	●
8.9	64	102	●
9	64	102	●
9.1	64	102	●
9.2	70	108	●
9.3	70	108	●
9.4	70	108	●
9.5	70	108	●
9.6	73	114	●
9.7	73	114	●
9.8	73	114	●
9.9	73	114	●
10	73	114	●
10.5	73	114	●
11	73	114	●
11.5	76	121	●
12	76	121	●

超微粒鎢鋼麻花鑽頭

Jobber Drills

118° Point for Quick Penetration

MG
CarbideUncoated
Bright

Code No: D453-DC



Work Material

P	H	M	K	N	S
○			●	●	

P	鋼鐵 Steel
---	-------------

K	鑄鐵 Cast Iron
---	-----------------

N	鋁 Aluminium
---	----------------

N	銅 Copper
---	-------------

N	塑膠 Plastics
---	----------------

N	複合材料 FRP CFRP Composite Material
---	-------------------------------------


Tolerance: DC

All Sizes: h7

Feature of product:

提供卓越的耐磨性。

用於抗拉強度較低的材料，如：鑄鐵、鑄鋁、青銅、銅、鋅、黃銅、橡膠、塑膠及複合材料等。鋼鐵也可適用於一般鑽孔加工。



Standard Length

Dc h7	Dec. Equiv. Inch	Lc Inch	L Inch	Bright D453
1/64	0.0156	3/16	3/4	●
1/32	0.0312	5/16	1-1/4	●
3/64	0.0469	3/4	1-1/2	●
1/16	0.0625	3/4	1-1/2	●
5/64	0.0781	7/8	1-3/4	●
3/32	0.0938	1	2	●
7/64	0.1094	1-1/4	2-1/4	●
1/8	0.1250	1-1/4	2-1/4	●
9/64	0.1406	1-3/8	2-1/2	●
5/32	0.1562	1-3/8	2-1/2	●
11/64	0.1719	1-5/8	2-3/4	●
3/16	0.1875	1-5/8	2-3/4	●
13/64	0.2031	1-3/4	3	●
7/32	0.2188	1-3/4	3	●
15/64	0.2344	2	3-1/4	●
1/4	0.2500	2	3-1/4	●
17/64	0.2656	2-1/8	3-1/2	●
9/32	0.2812	2-1/8	3-1/2	●
19/64	0.2969	2-3/8	3-3/4	●
5/16	0.3125	2-3/8	3-3/4	●
21/64	0.3281	2-1/2	4	●
11/32	0.3438	2-1/2	4	●
23/64	0.3594	2-1/2	4-1/4	●
3/8	0.3750	2-3/4	4-1/4	●
25/64	0.3906	2-7/8	4-1/2	●
13/32	0.4062	2-7/8	4-1/2	●
27/64	0.4219	2-7/8	4-1/2	●
7/16	0.4375	2-7/8	4-1/2	●
29/64	0.4531	3	4-3/4	●
15/32	0.4688	3	4-3/4	●
31/64	0.4844	3	4-3/4	●
1/2	0.5000	3	4-3/4	●
17/32	0.5312	3-1/4	5	●
9/16	0.5625	3-1/4	5	●
5/8	0.6250	3-1/2	5-1/4	●
3/4	0.7500	3-7/8	5-3/4	●
#80	0.0135	3/16	3/4	●
#79	0.0145	3/16	3/4	●

Jobber Drills
118° Point for Quick Penetration



Code No: D453-DC

Standard Length

Work Material

P	H	M	K	N	S
○			●	●	

P 鋼鐵
Steel

K 鑄鐵
Cast Iron

N 鋁
Aluminium

N 銅
Copper

N 塑膠
Plastics

N 複合材料 FRP CFRP
Composite Material

Tolerance: DC

All Sizes: h7

Feature of product:

提供卓越的耐磨性。
用於抗拉強度較低的材料，如：鑄鐵、鑄鋁、青銅、銅、鋅、黃銅、橡膠、塑膠及複合材料等... 鋼鐵也可適用於一般鑽孔加工。

Dc h7	Dec. Equiv. Inch	Lc Inch	L Inch	Bright D453	Dc h7	Dec. Equiv. Inch	Lc Inch	L Inch	Bright D453
#78	0.0160	3/16	3/4	●	#26	0.1470	1-3/8	2-1/2	●
#77	0.0180	3/16	3/4	●	#25	0.1495	1-3/8	2-1/2	●
#76	0.0200	1/4	7/8	●	#24	0.1520	1-3/8	2-1/2	●
#75	0.0210	1/4	7/8	●	#23	0.1540	1-3/8	2-1/2	●
#74	0.0225	1/4	7/8	●	#22	0.1570	1-3/8	2-1/2	●
#73	0.0240	1/4	7/8	●	#21	0.1590	1-3/8	2-1/2	●
#72	0.0250	5/16	1	●	#20	0.1610	1-3/8	2-1/2	●
#71	0.0260	5/16	1	●	#19	0.1660	1-5/8	2-3/4	●
#70	0.0280	5/16	1	●	#18	0.1695	1-5/8	2-3/4	●
#69	0.0292	5/16	1	●	#17	0.1730	1-5/8	2-3/4	●
#68	0.0310	3/8	1-1/8	●	#16	0.1770	1-5/8	2-3/4	●
#67	0.0320	3/8	1-1/8	●	#15	0.1800	1-5/8	2-3/4	●
#66	0.0330	3/8	1-1/8	●	#14	0.1820	1-5/8	2-3/4	●
#65	0.0350	3/8	1-1/8	●	#13	0.1850	1-5/8	2-3/4	●
#64	0.0360	5/8	1-1/4	●	#12	0.1890	1-5/8	2-3/4	●
#63	0.0370	5/8	1-1/4	●	#11	0.1910	1-5/8	2-3/4	●
#62	0.0380	1/2	1-1/4	●	#10	0.1935	1-5/8	2-3/4	●
#61	0.0390	1/2	1-1/4	●	#9	0.1960	1-3/4	3	●
#60	0.0400	3/4	1-1/2	●	#8	0.1990	1-3/4	3	●
#59	0.0410	3/4	1-1/2	●	#7	0.2010	1-3/4	3	●
#58	0.0420	3/4	1-1/2	●	#6	0.2040	1-3/4	3	●
#57	0.0430	3/4	1-1/2	●	#5	0.2055	1-3/4	3	●
#56	0.0465	3/4	1-1/2	●	#4	0.2090	1-3/4	3	●
#55	0.0520	3/4	1-1/2	●	#3	0.2130	1-3/4	3	●
#54	0.0550	3/4	1-1/2	●	#2	0.2210	1-3/4	3	●
#53	0.0595	3/4	1-1/2	●	#1	0.2280	1-3/4	3	●
#52	0.0635	3/4	1-1/2	●	A	0.2340	2	3-1/4	●
#51	0.0670	3/4	1-1/2	●	B	0.2380	2	3-1/4	●
#50	0.0700	7/8	1-3/4	●	C	0.2420	2	3-1/4	●
#49	0.0730	7/8	1-3/4	●	D	0.2460	2	3-1/4	●
#48	0.0760	7/8	1-3/4	●	E	0.2500	2	3-1/4	●
#47	0.0785	7/8	1-3/4	●	F	0.2570	2	3-1/4	●
#46	0.0810	7/8	1-3/4	●	G	0.2610	2-1/8	3-1/2	●
#45	0.0820	7/8	1-3/4	●	H	0.2660	2-1/8	3-1/2	●
#44	0.0860	1	2	●	I	0.2720	2-1/8	3-1/2	●
#43	0.0890	1	2	●	J	0.2770	2-1/8	3-1/2	●
#42	0.0935	1	2	●	K	0.2810	2-1/8	3-1/2	●
#41	0.0960	1	2	●	L	0.2900	2-1/8	3-1/2	●
#40	0.0980	1	2	●	M	0.2950	2-3/8	3-3/4	●
#39	0.0995	1-1/4	2-1/4	●	N	0.3020	2-3/8	3-3/4	●
#38	0.1015	1-1/4	2-1/4	●	O	0.3160	2-3/8	3-3/4	●
#37	0.1040	1-1/4	2-1/4	●	P	0.3230	2-3/8	3-3/4	●
#36	0.1065	1-1/4	2-1/4	●	Q	0.3320	2-1/2	4	●
#35	0.1100	1-1/4	2-1/4	●	R	0.3390	2-1/2	4	●
#34	0.1110	1-1/4	2-1/4	●	S	0.3480	2-1/2	4	●
#33	0.1130	1-1/4	2-1/4	●	T	0.3580	2-1/2	4-1/4	●
#32	0.1160	1-1/4	2-1/4	●	U	0.3680	2-3/4	4-1/4	●
#31	0.1200	1-1/4	2-1/4	●	V	0.3770	2-3/4	4-1/4	●
#30	0.1285	1-1/4	2-1/4	●	W	0.3860	2-7/8	4-1/2	●
#29	0.1360	1-3/8	2-1/2	●	X	0.3970	2-7/8	4-1/2	●
#28	0.1405	1-3/8	2-1/2	●	Y	0.4040	2-7/8	4-1/2	●
#27	0.1440	1-3/8	2-1/2	●	Z	0.4130	2-7/8	4-1/2	●